

PARKSIDE

MORTON

PATTERNED PORCELAIN RANGE



7

COLOURS

1

SIZE

1

FINISH

0

SPECIAL PIECES

Morton is a porcelain tile range made up of seven 223x223mm squares. In addition to classic greys and blacks, this collection combines new shades of dark red, mustard, green and blue, with floral patterns that can be joined to create continuous designs.

This range is suitable for both wall and floor.

COLOURS AVAILABLE



SIZE GUIDE



PARKSIDE

PRODUCT DATA SHEET

MORTON



Dimensions	23.3x23.3x1cm
Finish	Matt
Body	Porcelain
Wall/Floor	Wall & Floor
Group	Bi _b
Pendulum Dry (4S)	36+
Pendulum Wet (4S)	36+
Pendulum Wet (TRL)	NPD

Available Sizes
23.3x23.3x1cm

Recycled Content	%
Morton	0%

	Standard	Requirement	Typical Test Value
Length & Width	ISO 10545-2	$\pm 0.6\% \leq 2\text{mm}$	Pass
Thickness	ISO 10545-2	$\pm 5\% \leq \pm 0.5\text{mm}$	Pass
Straightness	ISO 10545-2	$\pm 0.5\% \leq \pm 1.5\text{mm}$	Pass
Flatness	ISO 10545-2	$\pm 5\% \leq \pm 2.0\text{mm}$	Pass
Rectangularity	ISO 10545-2	$\pm 0.5\% \leq \pm 2.0\text{mm}$	Pass
Water Absorption	ISO 10545-3	$0.5\% \text{Eb} \geq 3\%$	Pass
Breaking strength	ISO 10545-4	$\geq 1100\text{N}$	Pass
Modulus of rupture	ISO 10545-4	30 N/mm ² Average min	Pass
Resistance to surface abrasion	ISO 10545-7	Complies with Standard	4
Frost Resistance	ISO 10545-12	Complies with Standard	Pass
Thermal Shock Resistance	ISO 10545-9	Complies with Standard	Pass
Resistance to Stain	ISO 10545-14	Min class 3	Pass
Resistance to chemicals	ISO 10545-14	Min Class B	Pass
Reaction to Fire	-	Floor/Wall class A1 FL/A1	Pass

The colour representations shown in this data sheet are as accurate as the limitations of the printing process will allow. Due to the manufacturing process of our floor tiles there may be a small variation in the PTV value. The slip resistance values are correct at the time of testing and represent the standard production value. Inadequate cleaning and maintenance will lead to significant reduction in the slip resistance of any tiles. The pendulum test results have been displayed in line with H&S Executive guidelines whereby 0-24 represents high slip potential, 25-35 moderate slip potential & 36+ represents a low slip potential