

PARKSIDE

LEON D'ORO

TERRAZZO & STONE EFFECT TILES



6

COLOURS

4

SIZES

2

FINISHES

0

SPECIAL PIECES

An exclusive collection, Leon d'Oro by 14oraitaliana is inspired by the original flooring in the Italian restaurant that shares the same name. The three luxurious colours are each complemented by a decorative piece crossed by golden lines inspired by ancient Euclidean geometrical shapes.




TALCO POLISHED




SELCE POLISHED



EMATITE POLISHED



FUMO POLISHED



FUMO MATT



TABACCO POLISHED



TABACCO MATT



VISONE POLISHED



VISONE MATT



TALCO DECOR



SELCE DECOR




EMATITE DECOR




FUMO DECOR



TABACCO DECOR



VISONE DECOR



HYPNOSE DECOR

PORCELAIN	10mm Thick		6mm Thick		Wall/Floor	Interior/ Exterior
	Matt	Polished	Matt	Polished	All Tiles	All Tiles
1200x1200	✓	✓			Wall & Floor	Interior
1200x2400	✓	✓			Wall & Floor	Interior
600x1200	✓	✓			Wall & Floor	Interior
600x600 Decor		✓			Wall	Interior
1200x2400 Regal				✓	Wall	Interior
1200x2400				✓	Wall	Interior
600x600 Hypnose			✓		Wall & Floor	Interior

Group	Bl _a			
		Standard	Requirement	Typical Test Value
Length & Width		ISO 10545-2	±0.6% ≤ 2mm	Pass
Thickness		ISO 10545-2	±5% ≤ ±0.5mm	Pass
Straightness		ISO 10545-2	±0.5% ≤ ±1.5mm	Pass
Flatness		ISO 10545-2	±0.5% ≤ ±2.0mm	Pass
Rectangularity		ISO 10545-2	±0.5% ≤ ±2.0mm	Pass
Water Absorption		ISO 10545-3	Eb ≤ 0.5%	Pass
Breaking strength		ISO 10545-4	≥ 1300N	Pass
Modulus of rupture		ISO 10545-4	35 N/mm ² Average min	Pass
Resistance to surface abrasion		ISO 10545-7	Min Class 3	PEI 4
Frost Resistance		ISO 10545-12	Complies with Standard	Pass
Thermal Shock Resistance		ISO 10545-9	Complies with Standard	Pass
Resistance to Stain		ISO 10545-14	Min Class 3	3/4
Resistance to chemicals		ISO 10545-14	Min Class B	Pass
Reaction to Fire		-	Floor/Wall class A1 FL/A1	Pass

The colour representations shown in this data sheet are as accurate as the limitations of the printing process will allow. Due to the manufacturing process of our floor tiles there may be a small variation in the PTV value. The slip resistance values are correct at the time of testing and represent the standard production value. Inadequate cleaning and maintenance will lead to significant reduction in the slip resistance of any tiles. The pendulum test results have been displayed in line with H&S Executive guidelines whereby 0-24 represents high slip potential, 25-35 moderate slip potential & 36+ represents a low slip potential