



**4**  
COLOURS

**3**  
SIZES

**1**  
FINISH

**0**  
SPECIAL PIECES



13%

Ravv is from the relation of materials with differently sized grains in four colours and two dimensional scales: micro and macro. Ravv is available in four natural colours and in three sizes. Two different decors complete the collection: Drops and Mosaic. Micro and Macro are available in 375x750mm and 750x750mm. Drops options are available in 750x750mm. Mosaic options are available in 300x300mm.



| Group                          | Bl <sub>a</sub> | RAVV                             |                    |
|--------------------------------|-----------------|----------------------------------|--------------------|
| PORCELAIN                      | 10mm Thick      |                                  | Wall/Floor         |
|                                | Matt            | Gloss                            | All Tiles          |
| 750x750                        | ✓               |                                  | Wall & Floor       |
| 375x750                        | ✓               |                                  | Wall & Floor       |
| 300x300 mosaic                 | ✓               |                                  | Wall & Floor       |
|                                | Standard        | Requirement                      | Typical Test Value |
| Length & Width                 | ISO 10545-2     | ±0.6% ≤ 2mm                      | Pass               |
| Thickness                      | ISO 10545-2     | ±5%<br>≤ ±0.5mm                  | Pass               |
| Straightness                   | ISO 10545-2     | ±0.5%<br>≤ ±1.5mm                | Pass               |
| Flatness                       | ISO 10545-2     | ±0.5%<br>≤ ±2.0mm                | Pass               |
| Rectangularity                 | ISO 10545-2     | ±0.5%<br>≤ ±2.0mm                | Pass               |
| Water Absorption               | ISO 10545-3     | Eb ≤ 0.5%                        | Pass               |
| Breaking strength              | ISO 10545-4     | ≥ 1300N                          | Pass               |
| Modulus of rupture             | ISO 10545-4     | 35 N/mm <sup>2</sup> Average min | Pass               |
| Resistance to surface abrasion | ISO 10545-7     | Min Class 3                      | PEI 5              |
| Frost Resistance               | ISO 10545-12    | Complies with Standard           | Pass               |
| Thermal Shock Resistance       | ISO 10545-9     | Complies with Standard           | Pass               |
| Resistance to Stain            | ISO 10545-14    | Min Class 3                      | 5                  |
| Resistance to chemicals        | ISO 10545-14    | Min Class B                      | Pass               |
| Reaction to Fire               | -               | Floor/Wall class A1 FL/A1        | Pass               |

| Recycled Content | %   |
|------------------|-----|
| Ravv             | 13% |

The colour representations shown in this data sheet are as accurate as the limitations of the printing process will allow. Due to the manufacturing process of our floor tiles there may be a small variation in the PTV value. The slip resistance values are correct at the time of testing and represent the standard production value. Inadequate cleaning and maintenance will lead to significant reduction in the slip resistance of any tiles. The pendulum test results have been displayed in line with H&S Executive guidelines whereby 0-24 represents high slip potential, 25-35 moderate slip potential & 36+ represents a low slip potential