



4

COLOURS

2

SIZES

2

FINISH

4

SPECIAL PIECES

An exclusive collection, Tahiti by 14oraitaliana is a collection with a strong and decisive character. The fashionable décor of stylised tropical leaves in 600x1200mm can be combined with the solid colour base tiles measuring 600x600mm.



FILODENDRO BASE



CHICORY BASE



COLEUS BASE



CARRUBA BASE



FILODENDRO DECOR



CHICORY DECOR



COLEUS DECOR



CARRUBA DECOR

PORCELAIN	10mm Thick		Wall/Floor
	Matt/Gloss Décor	Matt	All Tiles
600x1200	✓		Wall
600x600		✓	Wall & Floor

Group	BI _a
-------	-----------------

	Standard	Requirement	Typical Test Value
Length & Width	ISO 10545-2	±0.6% ≤ 2mm	Pass
Thickness	ISO 10545-2	±5% ≤ ±0.5mm	Pass
Straightness	ISO 10545-2	±0.5% ≤ ±1.5mm	Pass
Flatness	ISO 10545-2	±0.5% ≤ ±2.0mm	Pass
Rectangularity	ISO 10545-2	±0.5% ≤ ±2.0mm	Pass
Water Absorption	ISO 10545-3	Eb ≤ 0.5%	Pass
Breaking strength	ISO 10545-4	≥ 1300N	Pass
Modulus of rupture	ISO 10545-4	35 N/mm ² Average min	Pass
Resistance to surface abrasion	ISO 10545-7	Min Class 3	600 X 600 PEI 4 600 X 1200 PEI 3
Frost Resistance	ISO 10545-12	Complies with Standard	Pass
Thermal Shock Resistance	ISO 10545-9	Complies with Standard	Pass
Resistance to Stain	ISO 10545-14	Min Class 3	5
Resistance to chemicals	ISO 10545-14	Min Class B	Pass
Reaction to Fire	-	Floor/Wall class A1 FL/A1	Pass

Recycled Content	%
Tahiti	20%

The colour representations shown in this data sheet are as accurate as the limitations of the printing process will allow. Due to the manufacturing process of our floor tiles there may be a small variation in the PTV value. The slip resistance values are correct at the time of testing and represent the standard production value. Inadequate cleaning and maintenance will lead to significant reduction in the slip resistance of any tiles. The pendulum test results have been displayed in line with H&S Executive guidelines whereby 0-24 represents high slip potential, 25-35 moderate slip potential & 36+ represents a low slip potential