

PARKSIDE

STATINO

Marble Effect Collection



1

COLOURS

3

SIZES

2

FINISHES

2

SPECIAL PIECES

The green-blue hues of Amazonite shine through in this collection with a magical depth of colour that stimulates the senses. 6mm thick slabs are available in 600x1200, 1200x1200 and 1200x2400mm.

COLOURS AVAILABLE



PORCELAIN	6mm Thick		Wall/Floor
	Matt	Gloss	All Tiles
600X1200	✓	✓	Wall & Floor
1200X1200	✓	✓	Wall & Floor
1200X2400	✓	✓	Wall & Floor

PARKSIDE

PRODUCT DATA SHEET



Dimensions	Multiple
Finish	Matt &Gloss
Body	Porcelain
Wall/Floor	Wall & Floor
Interior/ Exterior	Interior
Group	Bla
Pendulum Dry (4S)	36+
Pendulum Wet (4S)	Tbc
Pendulum Wet (TRL)	tbc

Available Sizes (mm)		Standard	Requirement	Typical Test Value
600x1200	Length & Width	ISO 10545-2	$\pm 0.6\% \leq 2\text{mm}$	Pass
1200x1200	Thickness	ISO 10545-2	$\pm 5\%$ $\leq \pm 0.5\text{mm}$	Pass
1200x2400	Straightness	ISO 10545-2	$\pm 0.5\%$ $\leq \pm 1.5\text{mm}$	Pass
	Flatness	ISO 10545-2	$\pm 0.5\%$ $\leq \pm 2.0\text{mm}$	Pass
	Rectangularity	ISO 10545-2	$\pm 0.5\%$ $\leq \pm 2.0\text{mm}$	Pass
	Water Absorption	ISO 10545-3	$E_b \leq 0.5\%$	Pass
	Breaking strength	ISO 10545-4	$\geq 1300\text{N}$	Pass
	Modulus of rupture	ISO 10545-4	35 N/mm ² Average min	Pass
	Resistance to surface abrasion	ISO 10545-7	n/a	PEI 3
	Frost Resistance	ISO 10545-12	Complies with Standard	Pass
	Thermal Shock Resistance	ISO 10545-9	Complies with Standard	Pass
	Resistance to Stain	ISO 10545-14	Min class 3	Pass
	Resistance to chemicals	ISO 10545-14	Min Class B	Pass
	Reaction to Fire	-	Floor/Wall class A1 FL/A1	Pass

The colour representations shown in this data sheet are as accurate as the limitations of the printing process will allow. Due to the manufacturing process of our floor tiles there may be a small variation in the PTV value. The slip resistance values are correct at the time of testing and represent the standard production value. Inadequate cleaning and maintenance will lead to significant reduction in the slip resistance of any tiles. The pendulum test results have been displayed in line with H&S Executive guidelines whereby 0-24 represents high slip potential, 25-35 moderate slip potential & 36+ represents a low slip potential