

SHALTON

SLATE EFFECT TILES



3

COLOURS

2

SIZE

1


FINISH

0

SPECIAL PIECES

Shalton is a slate effect indoor & outdoor collection. The indoor tiles come in 2 sizes and 3 neutral colours and has a PTV 36+ finish. The outdoor 20mm tiles available in the Vista20 range come in all 3 colours and 3 formats making it a great solution for indoor/outdoor projects.

COLOURS AVAILABLE



SHALTON IVORY



SHALTON GREY



SHALTON BLACK

PORCELAIN	9mm Thick	Wall/Floor	Interior/ Exterior
	Matt	All Tiles	All Tiles
595x595	✓	Wall & Floor	Interior & Exterior
296.5x595	✓	Wall & Floor	Interior & Exterior
448x898		Floor	Exterior
595x595		Floor	Exterior
Modular 595x595, 295x595 & 295x295		Floor	Exterior

PRODUCT DATA SHEET

SHALTON – 9mm

Group	Bla - Porcelain
--------------	-----------------

	Standard	Requirements	Established Values
Length & Width	ISO 10545-2	±0.6% ~ ±2mm	Conforms
Thickness	ISO 10545-2	±5% ~ ±0.5mm	Conforms
Straightness	ISO 10545-2	±0.5% ~ ±1.5mm	Conforms
Flatness	ISO 10545-2	±0.5% ~ ±2.0mm	Conforms
Rectangularity	ISO 10545-2	±0.5% ~ ±2.0mm	Conforms
Water absorption	ISO 10545-3	Eb ≤ 0.5 %	≤ 0.5 %
Breaking strength	ISO 10545-4	≥ 1300N	Ave ≥ 1300N
Modulus of rupture	ISO 10545-4	Ave Minimum 35 N/mm2	Ave Minimum 35 N/mm2
Resistance to deep abrasion	ISO 10545-7	Declare Class	PEI 4
Thermal shock resistance	ISO 10545-9	Pass according to EN ISO 10545-1	Resistant
Frost Resistance	ISO 10545-12	Pass according to EN ISO 10545-1	Resistant
Resistance to household chemicals and swimming pool salts	ISO 10545-13	Min Class GB	GA
Resistance to high concentrations of alkalis and acids	ISO 10545-13	Declare Value	GHB
Resistance to low concentrations of alkalis and acids	ISO 10545-13	Declare Value	GLB
Resistance to Stain	ISO 10545-14	Declare Value	Class 5
Reaction to Fire	-	Class A1 A1/FL	A1 A1/FL

Slip Resistance Characteristics	Pendulum Dry (4S Slider 96) +36 PTV	Pendulum Wet (4S Slider 96) +36 PTV	Pendulum Wet (4S Slider 55) +36 PTV
Range	✓	✓	✓

The colour representations shown in this data sheet are as accurate as the limitations of the printing process will allow. Due to the manufacturing process of our floor tiles there may be a small variation in the PTV value. The slip resistance values are correct at the time of testing and represent the standard production value. Inadequate cleaning and maintenance will lead to significant reduction in the slip resistance of any tiles. The pendulum test results have been displayed in line with H&S Executive guidelines whereby 0-24 represents high slip potential, 25-35 moderate slip potential & 36+ represents a low slip potential

FOR FURTHER INFORMATION CONTACT: T: 0116 276 2532 – W: www.parkside.co.uk – E: info@parkside.co.uk

Strata Technical Tiles is the partner brand of Parkside Architectural Tiles