



6

COLOURS

6

SIZES

4

FINISHES

5


SPECIAL PIECES

Lido is a beautiful, technical porcelain collection.


Lido has rectified edges and subtle variation within the design with good anti slip properties.

Featuring multiple finishes, sizes and colours there is no limit to its capabilities.


COLOURS AVAILABLE




Anthracite



Grey



Silver



Mud



Bone



White

SPECIAL PIECES



Decor



Arrows



Triangle


FINISHES

	Soft	Matt	Semi-polished	Structured
900x900	✓	✓	✓	✓
600x600	✓	✓	✓	✓
450x450	✓			
45x900	✓			
300x600	✓			
100x600	✓		✓	
Décor	✓			
Arrow 1 & 2	✓		✓	
Triangle	✓		✓	
Mosaic	✓		✓	




SIZE GUIDE

900x900x10.5mm



600x600x10mm



450x450x8mm



450x900x10.5mm



300x600x10mm




100x600x10mm




SPECIAL PIECES



Decor
450x900x10.5mm



Arrow
348x148mm



Mosaic
300x300mm



Triangle
86x296mm



Dimensions	Multiple
Finish	Multiple
Body	Porcelain
Wall/Floor	Wall & Floor
Interior/Exterior	Interior & Exterior
Group	Bla
Pendulum Dry (4S)	36+
Pendulum Wet (4S)	24-35

Available Sizes	Standard	Requirement	Typical Test Value	
900x900x10.5mm 600x600x10mm 450x450x8mm 450x900x10.5mm 300x600x10mm 100x600x10mm 450x900x10.5mm Décor 348x148mm Arrow 86x296mm Triangle 300x300mm Mosaic	Length & Width	ISO 10545-2	$\pm 0.6\% \leq 2\text{mm}$	Pass
	Thickness	ISO 10545-2	$\pm 5\%$ $\leq \pm 0.5\text{mm}$	Pass
	Straightness	ISO 10545-2	$\pm 0.5\%$ $\leq \pm 1.5\text{mm}$	Pass
	Flatness	ISO 10545-2	$\pm 0.5\%$ $\leq \pm 2.0\text{mm}$	Pass
	Rectangularity	ISO 10545-2	$\pm 0.5\%$ $\leq \pm 2.0\text{mm}$	Pass
	Water Absorption	ISO 10545-3	$E_b \leq 0.5\%$	Pass
	Breaking strength	ISO 10545-4	$\geq 1300\text{N}$	Pass
	Modulus of rupture	ISO 10545-4	35 N/mm ² Average min	Pass
	Resistance to surface abrasion	ISO 10545-7	n/a	NPD
	Frost Resistance	ISO 10545-12	Complies with Standard	Pass
	Thermal Shock Resistance	ISO 10545-9	Complies with Standard	Pass
	Resistance to Stain	ISO 10545-14	Min class 3	Pass
	Resistance to chemicals	ISO 10545-14	Min Class B	Pass
	Reaction to Fire	-	Floor/Wall class A1 FL/A1	Pass

The colour representations shown in this data sheet are as accurate as the limitations of the printing process will allow. Due to the manufacturing process of our floor tiles there may be a small variation in the PTV value. The slip resistance values are correct at the time of testing and represent the standard production value. Inadequate cleaning and maintenance will lead to significant reduction in the slip resistance of any tiles. The pendulum test results have been displayed in line with H&S Executive guidelines whereby 0-24 represents high slip potential, 25-35 moderate slip potential & 36+ represents a low slip potential