

PARKSIDE

ERNESS

MARBLE EFFECT GLAZED PORCELAIN



42%

3

COLOURS

1

SIZE

2

FINISHES

0

SPECIAL PIECES

Erness is an ultra classy tile collection replicating the look of marble. Available in 2 natural colours and 2 finishes, Erness is an XL format tile which is perfect for creating seamless open living spaces.

This range has 42% recycled content.

COLOURS AVAILABLE



WHITE



ARGENT



SMOKE

SIZE GUIDE

900x900mm





Dimensions	900x900x12mm
Finish	Gloss and Matt
Body	Porcelain
Wall/Floor	Wall & Floor
Group	BI _a
Pendulum Dry	TBC
Pendulum Wet	TBC

Available Sizes
900x900x12mm

Due to the size & weight of the tile we recommend a minimum of two people lift and fix tiles.

Recycled Content	%
Erness	42%

	Standard	Requirement	Typical Test Value
Length & Width	ISO 10545-2	$\pm 0.6\% \leq 2\text{mm}$	Pass
Thickness	ISO 10545-2	$\pm 5\%$ $\leq \pm 0.5\text{mm}$	Pass
Straightness	ISO 10545-2	$\pm 0.5\%$ $\leq \pm 1.5\text{mm}$	Pass
Flatness	ISO 10545-2	$\pm 0.5\%$ $\leq \pm 2.0\text{mm}$	Pass
Rectangularity	ISO 10545-2	$\pm 0.5\%$ $\leq \pm 2.0\text{mm}$	Pass
Water Absorption	ISO 10545-3	$E_b \leq 0.5\%$	Pass
Breaking strength	ISO 10545-4	$\geq 1300\text{N}$	Pass
Modulus of rupture	ISO 10545-4	35 N/mm ² Average min	Pass
Resistance to surface abrasion	ISO 10545-7	n/a	NPD
Frost Resistance	ISO 10545-12	Complies with Standard	Pass
Thermal Shock Resistance	ISO 10545-9	Complies with Standard	Pass
Resistance to Stain	ISO 10545-14	Min class 3	Pass
Resistance to chemicals	ISO 10545-14	Min Class B	Pass
Reaction to Fire	-	Floor/Wall class A1 FL/A1	Pass

The colour representations shown in this data sheet are as accurate as the limitations of the printing process will allow. Due to the manufacturing process of our floor tiles there may be a small variation in the PTV value. The slip resistance values are correct at the time of testing and represent the standard production value. Inadequate cleaning and maintenance will lead to significant reduction in the slip resistance of any tiles. The pendulum test results have been displayed in line with H&S Executive guidelines whereby 0-24 represents high slip potential, 25-35 moderate slip potential & 36+ represents a low slip potential