

Halford

10 COLOURS / 1 SIZE / 1 FINISH / 0 SPECIAL PIECES

Halford is a glossy glazed ceramic wall tile collection. With 10 versatile, desirable colours any design scheme can be accommodated. This range has 10% recycled content.



Halford



Halford



Halford



MINT



LAVENDER



SKY



MIST



OCRE



MUSHROOM



WHITE



TEAL



BLUE



BONE

The colour representations shown in this data sheet are as accurate as the limitations of the printing process will allow. Due to the manufacturing process of our floor tiles there may be a small variation in the PTV value. The slip resistance values are correct at the time of testing and represent the standard production value. Inadequate cleaning and maintenance will lead to significant reduction in the slip resistance of any tiles. The pendulum test results have been displayed in line with H&S Executive guidelines whereby 0-24 represents high slip potential, 25-35 moderate slip potential & 36+ represents a low slip potential.

For further information contact: T: 0116 276 2532 – W: www.parkside.co.uk – E: info@parkside.co.uk

Strata Technical Tiles is the partner brand of Parkside Architectural Tiles

Halford



97x297

| | |
|------------------|-----------------|
| Dimensions | 297x97x9mm |
| Finish | Gloss |
| Body | Ceramic |
| Wall/floor | Wall |
| Group | BI _b |
| Pendulum Dry | – |
| Pendulum Wet | – |
| Recycled content | 10% |

| | Standard | Requirement | Typical test value |
|--|--------------|---|--------------------|
| Length and width Länge und Breite | ISO 10545-2 | ±0.6% ~ ±2mm | Pass Pas |
| Thickness | ISO 10545-2 | ±5% ≤ ±0.5mm | Pass |
| Straightness | ISO 10545-2 | ±0.5% ≤ ±1.5mm | Pass |
| Flatness | ISO 10545-2 | ±0.5% ≤ ±2.0mm | Pass |
| Rectangularity | ISO 10545-2 | ±0.5% ≤ ±2.0mm | Pass |
| Water absorption | ISO 10545-3 | 6% < E _b ≤ 10% | Pass |
| Breaking strength | ISO 10545-4 | ≥ 800N | Pass |
| Modulus of rupture Bruchmodul | ISO 10545-4 | Ave Minimum 18 N/mm ² | Pass |
| Resistance to surface abrasion | ISO 10545-7 | n/a | n/a |
| Frost resistance | ISO 10545-12 | Complies with Standard | Not resistant |
| Thermal shock resistance | ISO 10545-9 | Complies with Standard | Pass |
| Resistance to stain | ISO 10545-14 | Min Class 3 | Pass |
| Resistance to chemicals Beständigkeit gegenüber Chemikalien | ISO 10545-14 | Min Class B Min. Klasse B | Pass |
| Reaction to fire Reaktion auf Feuer | - | Floor/wall Class A1 A1/FL Boden/Wand Klasse A1 A1/FL | Pass |

The colour representations shown in this data sheet are as accurate as the limitations of the printing process will allow. Due to the manufacturing process of our floor tiles there may be a small variation in the PTV value. The slip resistance values are correct at the time of testing and represent the standard production value. Inadequate cleaning and maintenance will lead to significant reduction in the slip resistance of any tiles. The pendulum test results have been displayed in line with H&S Executive guidelines whereby 0-24 represents high slip potential, 25-35 moderate slip potential & 36+ represents a low slip potential.

For further information contact: T: 0116 276 2532 – W: www.parkside.co.uk – E: info@parkside.co.uk

Strata Technical Tiles is the partner brand of Parkside Architectural Tiles