

Welford

54 COLOURS / 4 SIZES / 1 FINISHES / 0 SPECIAL PIECES

Welford presents a spectrum of 54 colours, all available in a matt finish. The mix of colours allows a variety of feelings to be conveyed with dark, muted tones through to cool and light hues. The Touch decor pieces are available in 200x200mm only.



Welford




Welford



AMARELO M257



AMARELO M258



AMARELO M259



ANTHRACITE M470




AZUL M140




AZUL M142




AZUL M144



AZUL M145



AZUL M146



AZUL M1149



AZUL M1151



AZUL M1152



AZUL M1153



BEGE M110




BEGE M111




BORDEAUX M171



BORDEAUX M172




CAMURCA M450



CASTANHO
ESCURO M490




CASTANHO M131




CASTANHO M132



CASTANHO M133



CINZA M121



CINZA M122



CINZA M123



CINZA M124




CINZA M125




LARANJA M500




LARANJA M501




NEVE M100



PASTEL M180



PEROLA M190



PRETO M200



VIOLETA M555



ROSA M162




ROSA M165



ROSA M166



ROSA M167



VERDE M150



VERDE M151



VERDE M152



VERDE M156



VERDE M157



VERMELHO M300

Welford




NEVE M100 TOUCH



CINZA M122 TOUCH



CINZA M123 TOUCH




NEVE M125 TOUCH



PRETO M200 TOUCH



PEROLA M100 TOUCH



CASTANHO M133 TOUCH



AMARELO M258 TOUCH



ROSA M167 TOUCH



AZUL M142 TOUCH

Sizes	Colours
200x200	All colours
100x200	Neve M100, Cinza M121, Cinza M122, Cinza M123, Cinza M124, Preto M200, Perola M190, Pastel M180, Bege M110, Laranja M500, Castanho M132, Amarelo M258, Vermelho M300, Rosa M167, Rosa M165, Bordeaux M172, Violeta M555, Azul M140, Azul M142, Azul M144, Verde M150 and Verde M152
150x150 and 100x100	Neve M100, Cinza M121, Cinza M123, Preto M200, Perola M190, Bege M110, Amarelo M258, Azul M140 and Azul M142

Porcelain	6mm thick	Wall/floor
	Matt	All tiles
100x100	✓	Wall
150x150	✓	Wall
200x200	✓	Wall
100x200	✓	Wall

The Touch decor pieces are available in 200x200mm only.

The colour representations shown in this data sheet are as accurate as the limitations of the printing process will allow. Due to the manufacturing process of our floor tiles there may be a small variation in the PTV value. The slip resistance values are correct at the time of testing and represent the standard production value. Inadequate cleaning and maintenance will lead to significant reduction in the slip resistance of any tiles. The pendulum test results have been displayed in line with H&S Executive guidelines whereby 0-24 represents high slip potential, 25-35 moderate slip potential & 36+ represents a low slip potential.

For further information contact: T: 0116 276 2532 – W: www.parkside.co.uk – E: info@parkside.co.uk

Strata Technical Tiles is the partner brand of Parkside Architectural Tiles

Welford

GROUP / Bla - PORCELAIN

Range	Standard	Requirement	Established Values
Length and width	ISO 10545-2	$\pm 0.6\% \sim \pm 2\text{mm}$	Conforms
Thickness	ISO 10545-2	$\pm 5\% \sim \pm 0.5\text{mm}$	Conforms
Straightness	ISO 10545-2	$\pm 0.5\% \sim \pm 1.5\text{mm}$	Conforms
Flatness	ISO 10545-2	$\pm 0.5\% \sim \pm 2.0\text{mm}$	Conforms
Rectangularity	ISO 10545-2	$\pm 0.5\% \sim \pm 2.0\text{mm}$	Conforms
Water absorption	ISO 10545-3	$E_b \leq 0.5\%$	$\leq 0.5\%$
Breaking strength	ISO 10545-4	$\geq 1300\text{N}$	$\geq 1300\text{N}$
Modulus of rupture	ISO 10545-4	Ave min 35 N/mm ²	Ave 35 N/mm ²
Resistance to surface abrasion	ISO 10545-7	Declare Class	n/a wall tile
Thermal shock resistance	ISO 10545-9	Pass according to EN ISO 10545-1	Resistant
Frost resistance	ISO 10545-12	Pass according to EN ISO 10545-1	Resistant
Resistance to household chemicals and swimming pool salts	ISO 10545-13	Min Class GB	GA
Resistance to high concentrations of alkalis and acids	ISO 10545-13	Declare Value	GHA
Resistance to low concentrations of alkalis and acids	ISO 10545-13	Declare Value	GLA
Resistance to stain	ISO 10545-14	Declare Value	Class 3
Reaction to fire	-	Class A1 A1/FL	A1 A1/FL

Recycled content	%
Welford	0

The colour representations shown in this data sheet are as accurate as the limitations of the printing process will allow. Due to the manufacturing process of our floor tiles there may be a small variation in the PTV value. The slip resistance values are correct at the time of testing and represent the standard production value. Inadequate cleaning and maintenance will lead to significant reduction in the slip resistance of any tiles. The pendulum test results have been displayed in line with H&S Executive guidelines whereby 0-24 represents high slip potential, 25-35 moderate slip potential & 36+ represents a low slip potential.

For further information contact: T: 0116 276 2532 – W: www.parkside.co.uk – E: info@parkside.co.uk

Strata Technical Tiles is the partner brand of Parkside Architectural Tiles