

# AZLETT

## Terrazzo Effect Tiles

7 COLOURS / 8 SIZES / 3 FINISHES / 0 SPECIAL PIECES

Azlett is a comprehensive collection of extruded, unglazed, full body porcelain tiles. A high quality product with a homogenous surface and body ensuring longevity in even the most demanding of environments.

There are 3 finish options - Natural, Satin and Cl.

This range has 15% recycled content.



Porcelain	8mm			6mm		7mm		14mm		12mm			Wall/ Floor	Interior/ Exterior	
	Nat	Cl	Sat	Nat	Cl	Nat	Cl	Nat	Nat	Cl	Text Cl	AS	Drain Text	All Tile	All Tile
295x592	✓	✓	✓											Wall and floor	Interior & exterior
592x592	✓	✓	✓											Wall and floor	Interior & exterior
392x392	✓	✓	✓											Wall and floor	Interior & exterior
295x295	✓	✓	✓					✓*	✓*	✓*	✓*	✓*	✓*	Wall and floor	Interior & exterior
300x300	✓	✓		✓	✓			✓*	✓*	✓*	✓*	✓*	✓*	Wall and floor	Interior & exterior
200x200						✓	✓	✓*	✓*	✓*	✓*	✓*	✓*	Wall and floor	Interior & exterior
194x194						✓	✓	✓*	✓*	✓*	✓*	✓*	✓*	Wall and floor	Interior & exterior
117x240									✓*	✓*				Wall and floor	Interior & exterior

# AZLETT

## Terrazzo Effect Tiles

### Group | Ala – Porcelain

	Standard	Requirements	Established Values
Length & Width	ISO 10545-2	±1.0% ~ ±2mm	Conforms
Thickness	ISO 10545-2	±10%	Conforms
Straightness	ISO 10545-2	±0.5%	Conforms
Flatness	ISO 10545-2	±0.5%	Conforms
Rectangularity	ISO 10545-2	±1%	Conforms
Water absorption	ISO 10545-3	Eb ≤ 0.5%	≤ 0.5%
Breaking strength	ISO 10545-4	≥ 7.5 mm thickness - ≥ 1300N < 7.5 mm thickness - < 600N	≥ 7.5 mm thickness - ≥ 1300N < 600N
Modulus of rupture	ISO 10545-4	Ave Minimum 28 N/mm <sup>2</sup>	Ave Minimum 28 N/mm <sup>2</sup>
Resistance to deep abrasion (unglazed tiles)	ISO 10545-6	Maximum 275mm <sup>2</sup>	Ave <150mm <sup>2</sup>
Thermal shock resistance	ISO 10545-9	Pass according to EN ISO 10545-1	Resistant
Frost Resistance	ISO 10545-12	Pass according to EN ISO 10545-1	Resistant
Resistance to household chemicals and swimming pool salts	ISO 10545-13	Min Class UB	Class UA
Resistance to high concentrations of alkalis and acids	ISO 10545-13	Declare Value	Class UHA
Resistance to low concentrations of alkalis and acids	ISO 10545-13	Declare Value	Class ULA
Resistance to Stain	ISO 10545-14	Declare Value	Class 3
Reaction to Fire	-	Class A1 A1/FL	A1 A1/FL
Slip Resistance Characteristics	Pendulum Dry (4S Slider 96) +36 PTV	Pendulum Wet (4S Slider 96) +36 PTV	
C1 & AS Finish Only	✓	✓	
Recycled Content	Pendulum Dry (4S Slider 96) +36 PTV		
Azlett	15%		

The colour representations shown in this data sheet are as accurate as the limitations of the printing process will allow. Due to the manufacturing process of our floor tiles there may be a small variation in the PTV value. The slip resistance values are correct at the time of testing and represent the standard production value. Inadequate cleaning and maintenance will lead to significant reduction in the slip resistance of any tiles. The pendulum test results have been displayed in line with H&S Executive guidelines whereby 0-24 represents high slip potential, 25-35 moderate slip potential & 36+ represents a low slip potential

For further information contact: T: 0116 276 2532 – W: [www.parkside.co.uk](http://www.parkside.co.uk) – E: [info@parkside.co.uk](mailto:info@parkside.co.uk)

**Strata Technical Tiles is the partner brand of Parkside Architectural Tiles**

# AZLETT

## Terrazzo Effect Tiles

	Standard	Requirements	Established Values
Length & Width	ISO 10545-2	±0.6% ~ ±2mm	Conforms
Thickness	ISO 10545-2	±5% ~ ±0.5mm	Conforms
Straightness	ISO 10545-2	±0.5% ~ ±1.5mm	Conforms
Flatness	ISO 10545-2	±0.5% ~ ±2.0mm	Conforms
Rectangularity	ISO 10545-2	±0.5% ~ ±2.0mm	Conforms
Water absorption	ISO 10545-3	Eb ≤ 0.5%	Ave ≤ 0.06%
Breaking strength	ISO 10545-4	≥ 700N (for thickness < 7,5mm) ≥ 1300N (for thickness ≥ 7,5mm)	Ave ≥ 700N Ave 2500N
Modulus of rupture	ISO 10545-4	Ave Minimum 35 N/mm <sup>2</sup>	Ave Minimum 50 N/mm <sup>2</sup>
Resistance to deep abrasion (unglazed tiles)	ISO 10545-6	< 175mm <sup>3</sup>	Ave 142mm <sup>3</sup>
Thermal shock resistance	ISO 10545-9	Pass according to EN ISO 10545-1	Resistant
Frost Resistance	ISO 10545-12	Pass according to EN ISO 10545-1	Resistant
Resistance to household chemicals and swimming pool salts	ISO 10545-13	Min Class UB	UB
Resistance to high concentrations of alkalis and acids	ISO 10545-13	Declare Value	NPD
Resistance to low concentrations of alkalis and acids	ISO 10545-13	Declare Value	NPD
Resistance to Stain	ISO 10545-14	Declare Value	Class 5
Reaction to Fire	-	Class A1 A1/FL	A1 A1/FL
Slip Resistance Characteristics	Pendulum Dry (4S Slider 96) +36 PTV	Pendulum Wet (4S Slider 96) +36 PTV	
Structured Finish	✓	✓	

The colour representations shown in this data sheet are as accurate as the limitations of the printing process will allow. Due to the manufacturing process of our floor tiles there may be a small variation in the PTV value. The slip resistance values are correct at the time of testing and represent the standard production value. Inadequate cleaning and maintenance will lead to significant reduction in the slip resistance of any tiles. The pendulum test results have been displayed in line with H&S Executive guidelines whereby 0-24 represents high slip potential, 25-35 moderate slip potential & 36+ represents a low slip potential

For further information contact: T: 0116 276 2532 – W: [www.parkside.co.uk](http://www.parkside.co.uk) – E: [info@parkside.co.uk](mailto:info@parkside.co.uk)

**Strata Technical Tiles is the partner brand of Parkside Architectural Tiles**

# AZLETT

## Terrazzo Effect Tiles




PEROLA CI



BEGE CI



CLARO CI



WHITE LITHOS



ALUMINIO CI



PRETO CI



BLACK CI

The colour representations shown in this data sheet are as accurate as the limitations of the printing process will allow. Due to the manufacturing process of our floor tiles there may be a small variation in the PTV value. The slip resistance values are correct at the time of testing and represent the standard production value. Inadequate cleaning and maintenance will lead to significant reduction in the slip resistance of any tiles. The pendulum test results have been displayed in line with H&S Executive guidelines whereby 0-24 represents high slip potential, 25-35 moderate slip potential & 36+ represents a low slip potential

For further information contact: T: 0116 276 2532 – W: [www.parkside.co.uk](http://www.parkside.co.uk) – E: [info@parkside.co.uk](mailto:info@parkside.co.uk)

**Strata Technical Tiles is the partner brand of Parkside Architectural Tiles**