

Bastoni

25 DESIGNS / MATT AND GLOSS FINISHES

The “kit kat mosaic” is ideal for creating feature spaces. Bastoni comes in so many colours and designs; there’s something to suit any area.



Bastoni



Bastoni




WHITE PICCOLO MATT



WHITE PICCOLO GLOSS



GREY BLUE SPECKLE PICCOLO




AZURE BLUE SPECKLE PICCOLO



BLACK PICCOLO MATT



LIGHT GREEN SPECKLE PICCOLO



BLACK PICCOLO GLOSS



SOFT WHITE PICCOLO GLOSS



TURQUOISE GRANDE



RED SPECKLE GRANDE



BLUE GRANDE



GREEN SPECKLE GRANDE



OCEAN GREEN GRANDE



BLUE GREY GRANDE



GREY SPECKLE GRANDE



WHITE SPECKLE GRANDE

The colour representations shown in this data sheet are as accurate as the limitations of the printing process will allow. Due to the manufacturing process of our floor tiles there may be a small variation in the PTV value. The slip resistance values are correct at the time of testing and represent the standard production value. Inadequate cleaning and maintenance will lead to significant reduction in the slip resistance of any tiles. The pendulum test results have been displayed in line with H&S Executive guidelines whereby 0-24 represents high slip potential, 25-35 moderate slip potential & 36+ represents a low slip potential.

For further information contact: T: 0116 276 2532 – W: www.parkside.co.uk – E: info@parkside.co.uk

Strata Technical Tiles is the partner brand of Parkside Architectural Tiles

Bastoni



CAFÉ LATTE GLOSS




WHITE GRANDE GLOSS




WHITE GRANDE MATT



VINTAGE WHITE GRANDE GLOSS



BLACK GRANDE MATT



BLACK GRANDE GLOSS



VANILLE GRANDE



CRÈME CARAMEL



BRONZE

Porcelain	8mm thick		Wall/floor	Interior/exterior
	Matt	Gloss	All tiles	All tiles
282x308	✓	✓	Wall Only	Interior Only
296x299	✓	✓	Wall Only	Interior Only

The colour representations shown in this data sheet are as accurate as the limitations of the printing process will allow. Due to the manufacturing process of our floor tiles there may be a small variation in the PTV value. The slip resistance values are correct at the time of testing and represent the standard production value. Inadequate cleaning and maintenance will lead to significant reduction in the slip resistance of any tiles. The pendulum test results have been displayed in line with H&S Executive guidelines whereby 0-24 represents high slip potential, 25-35 moderate slip potential & 36+ represents a low slip potential.

For further information contact: T: 0116 276 2532 – W: www.parkside.co.uk – E: info@parkside.co.uk

Strata Technical Tiles is the partner brand of Parkside Architectural Tiles

Bastoni

GROUP / Bia - PORCELAIN

	Standard	Requirement	Established Values
Length and Width	ISO 10545-2	±0.6% ~ ±2mm	Conforms
Thickness	ISO 10545-2	±5% ~ ±0.5mm	Conforms
Straightness	ISO 10545-2	±0.5% ~ ±1.5mm	Conforms
Flatness	ISO 10545-2	±0.5% ~ ±2.0mm	Conforms
Rectangularity	ISO 10545-2	±0.5% ~ ±2.0mm	Conforms
Water Absorption	ISO 10545-3	$E_w \leq 0.5\%$	Ave 0.13%
Breaking Strength	ISO 10545-4	$\geq 1300N$	1719N
Modulus of Rupture	ISO 10545-4	Ave Minimum 35 N/mm ²	49.5 N/mm ²
Resistance to deep abrasion (glazed tiles)	ISO 10545-7	Declare Value	PEI 3
Thermal Shock Resistance	ISO 10545-9	Pass according to EN ISO 10545-1	Pass
Frost Resistance	ISO 10545-12	Pass according to EN ISO 10545-1	Pass
Resistance to household chemicals and swimming pool salts	ISO 10545-13	Min Class GB	GA
Resistance to high concentrations of alkalis and acids	ISO 10545-13	Declare Value	GHA
Resistance to low concentrations of alkalis and acids	ISO 10545-13	Declare Value	GLA
Resistance to Stain	ISO 10545-14	Declare Value	Class 5
Reaction to Fire		Class A1 A1/FL	Class A1

Recycled Content	0 %
Range Name	Bastoni

The colour representations shown in this data sheet are as accurate as the limitations of the printing process will allow. Due to the manufacturing process of our floor tiles there may be a small variation in the PTV value. The slip resistance values are correct at the time of testing and represent the standard production value. Inadequate cleaning and maintenance will lead to significant reduction in the slip resistance of any tiles. The pendulum test results have been displayed in line with H&S Executive guidelines whereby 0-24 represents high slip potential, 25-35 moderate slip potential & 36+ represents a low slip potential.

For further information contact: T: 0116 276 2532 – W: www.parkside.co.uk – E: info@parkside.co.uk

Strata Technical Tiles is the partner brand of Parkside Architectural Tiles