

# Flaunt

4 COLOURS / 1 SIZES / 2 FINISHES / 0 SPECIAL PIECES

Taking inspiration from the reeded surfaces reminiscent of art deco glamour, Flaunt is a collection of ceramic wall tiles that are available in a plain or 3D reeded decor option, allowing a combination of laying patterns and designs to be achieved. The colour palette focuses on earthy tones, incorporating soft sage and terracotta, complemented by a classic white and a subtle grey. Available in 225x75mm and a matt finish, Flaunt has 21% recycled content.



Flaunt



Flaunt



# Flaunt



WHITE



WHITE DECOR



SAGE



SAGE DECOR



STEEL



STEEL DECOR



TERRACOTTA



TERRACOTTA DECOR

White body ceramic	9mm thick	12mm thick	Wall/floor	Interior/exterior
	Matt	Matt	All tiles	All tiles
225x75	✓	✓	Wall	Interior

The colour representations shown in this data sheet are as accurate as the limitations of the printing process will allow. Due to the manufacturing process of our floor tiles there may be a small variation in the PTV value. The slip resistance values are correct at the time of testing and represent the standard production value. Inadequate cleaning and maintenance will lead to significant reduction in the slip resistance of any tiles. The pendulum test results have been displayed in line with H&S Executive guidelines whereby 0-24 represents high slip potential, 25-35 moderate slip potential & 36+ represents a low slip potential.

For further information contact: T: 0116 276 2532 – W: [www.parkside.co.uk](http://www.parkside.co.uk) – E: [info@parkside.co.uk](mailto:info@parkside.co.uk)

Strata Technical Tiles is the partner brand of Parkside Architectural Tiles

# Flaut

## GROUP / BIII - CERAMIC

	Standard	Requirement	Established values
Length and width	ISO 10545-2	±0.6% ~ ±2mm	Conforms
Thickness	ISO 10545-2	±5% ~ ±0.5mm	Conforms
Straightness	ISO 10545-2	±0.5% ~ ±1.5mm	Conforms
Flatness	ISO 10545-2	±0.5% ~ ±2.0mm	Conforms
Rectangularity	ISO 10545-2	±0.5% ~ ±2.0mm	Conforms
Water absorption	ISO 10545-3	$E_b \leq 10\%$	Ave >13%
Breaking strength	ISO 10545-4	≥ 600N	Ave 800N
Modulus of rupture	ISO 10545-4	Ave Minimum 12 N/mm <sup>2</sup>	Ave min 12 N/mm <sup>2</sup>
Thermal shock resistance	ISO 10545-9	Pass according to EN ISO 10545-1	Resistant
Frost resistance	ISO 10545-12	Pass according to EN ISO 10545-1	Resistant
Resistance to household chemicals and swimming pool salts	ISO 10545-13	Min Class GB	GA
Resistance to high concentrations of alkalis and acids	ISO 10545-13	Declare Value	NPD
Resistance to low concentrations of alkalis and acids	ISO 10545-13	Declare Value	NPD
Resistance to stain	ISO 10545-14	Min Class 3	Class 4
Reaction to fire	-	Class A1 A1/FL	A1 A1/FL

Recycled Content	21 %
Range Name	Flaut

The colour representations shown in this data sheet are as accurate as the limitations of the printing process will allow. Due to the manufacturing process of our floor tiles there may be a small variation in the PTV value. The slip resistance values are correct at the time of testing and represent the standard production value. Inadequate cleaning and maintenance will lead to significant reduction in the slip resistance of any tiles. The pendulum test results have been displayed in line with H&S Executive guidelines whereby 0-24 represents high slip potential, 25-35 moderate slip potential & 36+ represents a low slip potential.

For further information contact: T: 0116 276 2532 – W: [www.parkside.co.uk](http://www.parkside.co.uk) – E: [info@parkside.co.uk](mailto:info@parkside.co.uk)

Strata Technical Tiles is the partner brand of Parkside Architectural Tiles