

Bruar

4 COLOURS / 1 SIZES / 1 FINISHES / 0 SPECIAL PIECES

Beautiful rich colours and fabric inspired patterns makes Bruar a great option for any wall surface. The lightly rippled surface and rustic edges gives the collection a handmade feel. Each colour features complimentary décor tiles, 8 pattern designs created through reactive glazes offering a unique surface. This range has 70% recycled content.



Bruar



Bruar



BLUE



TEAL



IVORY



GREY

PATTERN DESIGNS



The colour representations shown in this data sheet are as accurate as the limitations of the printing process will allow. Due to the manufacturing process of our floor tiles there may be a small variation in the PTV value. The slip resistance values are correct at the time of testing and represent the standard production value. Inadequate cleaning and maintenance will lead to significant reduction in the slip resistance of any tiles. The pendulum test results have been displayed in line with H&S Executive guidelines whereby 0-24 represents high slip potential, 25-35 moderate slip potential & 36+ represents a low slip potential.

For further information contact: T: 0116 276 2532 – W: www.parkside.co.uk – E: info@parkside.co.uk

Strata Technical Tiles is the partner brand of Parkside Architectural Tiles

Bruar



300X75

Dimensions	75X300X10mm
Finish	Glossy
Body	Ceramic
Wall/floor	Wall
Group	BIII
Pendulum Dry	–
Pendulum Wet	–
Recycled content	70%

Range	Standard	Requirement	Typical test value
Length and width	ISO 10545-2	±0.6% ~ ±2mm	Pass
Thickness	ISO 10545-2	±5% ~ ±0.5mm	Pass
Straightness	ISO 10545-2	±0.5% ~ ±1.5mm	Pass
Flatness	ISO 10545-2	±0.5% ~ ±2.0mm	Pass
Rectangularity	ISO 10545-2	±0.5% ~ ±2.0mm	Pass
Water absorption	ISO 10545-3	$E_v \leq 10\%$	Pass
Breaking strength	ISO 10545-4	≥ 600N	Pass
Modulus of rupture	ISO 10545-4	12 N/mm ² Average min	Pass
Resistance to surface abrasion	ISO 10545-7	n/a	NPD
Frost resistance	ISO 10545-12	Complies with standard	Not resistant
Thermal shock resistance	ISO 10545-9	Complies with standard	Pass
Resistance to stain	ISO 10545-14	Min Class 3	Pass
Resistance to chemicals	ISO 10545-13	Min Class B	Pass
Reaction to fire	-	Floor/wall Class A1 FL/A1	Pass

The colour representations shown in this data sheet are as accurate as the limitations of the printing process will allow. Due to the manufacturing process of our floor tiles there may be a small variation in the PTV value. The slip resistance values are correct at the time of testing and represent the standard production value. Inadequate cleaning and maintenance will lead to significant reduction in the slip resistance of any tiles. The pendulum test results have been displayed in line with H&S Executive guidelines whereby 0-24 represents high slip potential, 25-35 moderate slip potential & 36+ represents a low slip potential.

For further information contact: T: 0116 276 2532 – W: www.parkside.co.uk – E: info@parkside.co.uk

Strata Technical Tiles is the partner brand of Parkside Architectural Tiles