

Glint

5 COLOURS / 3 SIZES / 1 FINISHES / 0 SPECIAL PIECES

Hand-craftsmanship and ever-changing materials recall a ceramic tradition in which imperfection and defects are an added benefit. Clear shade transitions embellished with dripping rust and iron, irregularities typical of the artisan production process. Strong shading, chipping and relief imperfections give the collection an exclusive look to wrap spaces in a newfound naturalness. Super-glossy concave and convex surfaces combined with three-dimensional structures bringing Glint to life. A palette of five colours, Bianco, Beige, Turchese, Giada and Grigio available in three different sizes: 100x100mm, 50x150mm and 75x200mm.




Glint




Glint



Glint



BIANCO GLOSS



BIANCO EGG



BIANCO EYE



BEIGE GLOSS




BEIGE EGG



BEIGE EYE



TURCHESE GLOSS




TURCHESE EGG



TURCHESE EYE



GIADA GLOSS




GIADA EGG



GIADA EYE



GRIGIO GLOSS



GRIGIO EGG



GRIGIO EYE

Available sizes

50x150

75x200


100x100

The colour representations shown in this data sheet are as accurate as the limitations of the printing process will allow. Due to the manufacturing process of our floor tiles there may be a small variation in the PTV value. The slip resistance values are correct at the time of testing and represent the standard production value. Inadequate cleaning and maintenance will lead to significant reduction in the slip resistance of any tiles. The pendulum test results have been displayed in line with H&S Executive guidelines whereby 0-24 represents high slip potential, 25-35 moderate slip potential & 36+ represents a low slip potential.

For further information contact: T: 0116 276 2532 – W: www.parkside.co.uk – E: info@parkside.co.uk

Strata Technical Tiles is the partner brand of Parkside Architectural Tiles

Glint



Ceramic	Wall/floor	
	Gloss	All tiles
50x150	✓	Wall
75x200	✓	Wall
100x100	✓	Wall

GROUP / Bla - PORCELAIN

	Standard	Requirement	Established values
Length and width	ISO 10545-2	±0.6% ~ ±2mm	Conforms
Thickness	ISO 10545-2	±5% ~ ±0.5mm	Conforms
Straightness	ISO 10545-2	±0.5% ~ ±1.5mm	Conforms
Flatness	ISO 10545-2	±0.5% ~ ±2.0mm	Conforms
Rectangularity	ISO 10545-2	±0.5% ~ ±2.0mm	Conforms
Water absorption	ISO 10545-3	$E_b \leq 0.5\%$	$\leq 0.5\%$
Breaking strength	ISO 10545-4	$\geq 1300N$	$\geq 1300N$
Modulus of rupture	ISO 10545-4	Ave min 35 N/mm ²	Ave min 35 N/mm ²
Resistance to surface abrasion	ISO 10545-7	Declare Class	PEI 3
Thermal shock resistance	ISO 10545-9	Pass according to EN ISO 10545-1	Resistant
Frost resistance	ISO 10545-12	Pass according to EN ISO 10545-1	Resistant
Resistance to household chemicals and swimming pool salts	ISO 10545-13	Min Class GB	GA
Resistance to high concentrations of alkalis and acids	ISO 10545-13	Declare Value	GHB
Resistance to low concentrations of alkalis and acids	ISO 10545-13	Declare Value	GLB
Resistance to stain	ISO 10545-14	Declare Value	Class 5
Reaction to fire	-	Class A1 A1/FL	A1 A1/FL

Recycled content	%
Glint	12

The colour representations shown in this data sheet are as accurate as the limitations of the printing process will allow. Due to the manufacturing process of our floor tiles there may be a small variation in the PTV value. The slip resistance values are correct at the time of testing and represent the standard production value. Inadequate cleaning and maintenance will lead to significant reduction in the slip resistance of any tiles. The pendulum test results have been displayed in line with H&S Executive guidelines whereby 0-24 represents high slip potential, 25-35 moderate slip potential & 36+ represents a low slip potential.

For further information contact: T: 0116 276 2532 – W: www.parkside.co.uk – E: info@parkside.co.uk

Strata Technical Tiles is the partner brand of Parkside Architectural Tiles