

# Kraus

**20 COLOURS / 3 SIZES / 1 FINISHES / 0 SPECIAL PIECES**

These luxury vinyl tiles, known as SPC (Stone Polymer Composite) are comprised of a rigid core for added durability. This glue-less format features an integral underlay and click locking system making it fast and easy to install with only a knife. Ideal for using throughout the home providing both heat and sound insulation, your space is transformed immediately as there's no setting time. 100% waterproof and a diamond coated finish, their natural texture makes it a hygienic, easy-to-clean flooring solution, resistant to scuffs and stains.




Kraus



# Kraus



GRASSMERE




KIELDER



ASHDOWN



HADLEY



WYCHWOOD



RYDALL




GRIZEDALE




SWINLEY



INGLETON



RIVINGTON




DELAMARE



EPPING



ENNERDALE




GILLOWSTONE




PARSONS




FURNESS



BIRKETT



MERCIA



STANHOPE



WINSPIT



610x305

## GROUP / LUXURY VINYL FLOORING RIGID TILE 61CM X 30.5CM

	Standard	Result
CE/DOP	BS EN 14041	Pass
Usage Classification	BS EN 485	23-31
Manufacturing Standard	BS EN 649	Pass
Total Thickness	BS EN 428	6mm
Wear Layer thickness	BS EN 429	0.3mm
Weight	BS EN 430	8.11 kg/m <sup>2</sup>
Abrasion Resistance	BS EN 660-1/2	Group T
Residual Indentation	BS EN 433	Pass
Dimensional Stability	BS EN 434	Pass
Chemical Resistance	BS EN 423	Pass
Colour Fastness to Light	BS EN 20105-B02	≥ 6 Class
Flammability	BS EN 13501-1-1 Class Bfl-S1	Pass
Caster Chair Resistance	BS EN 425	22034
Impact Sound Insulation	BS EN ISO 140-8	IIC=73 STC=72
Thermal Resistance	BS EN 12667	0.033(m <sup>2</sup> .k)/W
Electrostatic Performance	BS EN 1815	0.2 Kv
Emissions	Floor Score	Pass
Phthalate Free	BS EN 14372	Pass

Slip resistance characteristics	Pendulum Dry (4S Slider 96) +36 PTV	Pendulum Wet (4S Slider 96) +36 PTV
Full range	✓	✓

The colour representations shown in this data sheet are as accurate as the limitations of the printing process will allow. Due to the manufacturing process of our floor tiles there may be a small variation in the PTV value. The slip resistance values are correct at the time of testing and represent the standard production value. Inadequate cleaning and maintenance will lead to significant reduction in the slip resistance of any tiles. The pendulum test results have been displayed in line with H&S Executive guidelines whereby 0-24 represents high slip potential, 25-35 moderate slip potential & 36+ represents a low slip potential

For further information contact: T: 0116 276 2532 – W: [www.parkside.co.uk](http://www.parkside.co.uk) – E: [info@parkside.co.uk](mailto:info@parkside.co.uk)

Strata Technical Tiles is the partner brand of Parkside Architectural Tiles



1230x179

## GROUP / LUXURY VINYL FLOORING RIGID PLANK 123CM X 17.9CM

	Standard	Result
CE/DOP	BS EN 14041	Pass
Usage Classification	BS EN 485	23-31
Manufacturing Standard	BS EN 649	Pass
Total Thickness	BS EN 428	6mm
Wear Layer thickness	BS EN 429	0.3mm
Weight	BS EN 430	9.83 kg/m <sup>2</sup>
Abrasion Resistance	BS EN 660-1/2	Group T
Residual Indentation	BS EN 433	Pass
Dimensional Stability	BS EN 434	Pass
Chemical Resistance	BS EN 423	Pass
Colour Fastness to Light	BS EN 20105-B02	≥ 6 Class
Flammability	BS EN 13501-1-1 Class Bfl-S1	Pass
Caster Chair Resistance	BS EN 425	25322
Impact Sound Insulation	BS EN ISO 140-8	IIC=73 STC=72
Thermal Resistance	BS EN 12667	0.033(m <sup>2</sup> .k)/W
Electrostatic Performance	BS EN 1815	0.2 Kv
Emissions	Floor Score	Pass
Phthalate Free	BS EN 14372	Pass

Slip resistance characteristics	Pendulum Dry (4S Slider 96) +36 PTV	Pendulum Wet (4S Slider 96) +36 PTV
Full range	✓	✓

The colour representations shown in this data sheet are as accurate as the limitations of the printing process will allow. Due to the manufacturing process of our floor tiles there may be a small variation in the PTV value. The slip resistance values are correct at the time of testing and represent the standard production value. Inadequate cleaning and maintenance will lead to significant reduction in the slip resistance of any tiles. The pendulum test results have been displayed in line with H&S Executive guidelines whereby 0-24 represents high slip potential, 25-35 moderate slip potential & 36+ represents a low slip potential

For further information contact: T: 0116 276 2532 – W: [www.parkside.co.uk](http://www.parkside.co.uk) – E: [info@parkside.co.uk](mailto:info@parkside.co.uk)

Strata Technical Tiles is the partner brand of Parkside Architectural Tiles



1218x226

## GROUP / LUXURY VINYL FLOORING RIGID PLANK 121.8CM X 22.6CM

	Standard	Result
CE/DOP	BS EN 14041	Pass
Usage Classification	BS EN 485	23-31
Manufacturing Standard	BS EN 649	Pass
Total Thickness	BS EN 428	5mm
Wear Layer thickness	BS EN 429	0.5mm
Weight	BS EN 430	7.68 kg/m <sup>2</sup>
Abrasion Resistance	BS EN 660-1/2	Group T
Residual Indentation	BS EN 433	Pass
Dimensional Stability	BS EN 434	Pass
Chemical Resistance	BS EN 423	Pass
Colour Fastness to Light	BS EN 20105-B02	≥ 6 Class
Flammability	BS EN 13501-1-1 Class Bfl-S1	Pass
Caster Chair Resistance	BS EN 425	22130
Impact Sound Insulation	BS EN ISO 140-8	IIC=55 STC=49
Thermal Resistance	BS EN 12667	0.033(m <sup>2</sup> .k)/W
Electrostatic Performance	BS EN 1815	0.2 Kv
Emissions	Floor Score	Pass
Phthalate Free	BS EN 14372	Pass

Slip resistance characteristics	Pendulum Dry (4S Slider 96) +36 PTV	Pendulum Wet (4S Slider 96) +36 PTV
Full range	✓	✓

The colour representations shown in this data sheet are as accurate as the limitations of the printing process will allow. Due to the manufacturing process of our floor tiles there may be a small variation in the PTV value. The slip resistance values are correct at the time of testing and represent the standard production value. Inadequate cleaning and maintenance will lead to significant reduction in the slip resistance of any tiles. The pendulum test results have been displayed in line with H&S Executive guidelines whereby 0-24 represents high slip potential, 25-35 moderate slip potential & 36+ represents a low slip potential

For further information contact: T: 0116 276 2532 – W: [www.parkside.co.uk](http://www.parkside.co.uk) – E: [info@parkside.co.uk](mailto:info@parkside.co.uk)

Strata Technical Tiles is the partner brand of Parkside Architectural Tiles