

Morton

7 COLOURS / 1 SIZES / 1 FINISHES / 0 SPECIAL PIECES

Morton is a patterned porcelain tile range made up of seven 223x223mm squares. In addition to classic greys and blacks, this collection combines new shades of dark red, mustard, green and blue, with floral patterns that can be joined to create continuous designs. This range is suitable for both wall and floor.



Morton



Morton



Morton



BLOOM BLUE



BLOOM GREEN



DAISY BLUE



DAISY YELLOW



ARABIS



DAHLIA



IRIS



WHITE PETAL




WHITE CROSS

Dimensions	223x223x10mm
Finish	Matt
Body	Porcelain
Wall/floor	Wall and floor
Group	BI _a
Pendulum Dry (4S)	36+
Pendulum Wet (4S)	36+
Pendulum Wet (TRL)	NPD

The colour representations shown in this data sheet are as accurate as the limitations of the printing process will allow. Due to the manufacturing process of our floor tiles there may be a small variation in the PTV value. The slip resistance values are correct at the time of testing and represent the standard production value. Inadequate cleaning and maintenance will lead to significant reduction in the slip resistance of any tiles. The pendulum test results have been displayed in line with H&S Executive guidelines whereby 0-24 represents high slip potential, 25-35 moderate slip potential & 36+ represents a low slip potential.

For further information contact: T: 0116 276 2532 – W: www.parkside.co.uk – E: info@parkside.co.uk

Strata Technical Tiles is the partner brand of Parkside Architectural Tiles



223x223

	Standard	Requirement	Established values
Length and width	ISO 10545-2	±0.6% ~ ±2mm	Pass
Thickness	ISO 10545-2	±5% ~ ±0.5mm	Pass
Straightness	ISO 10545-2	±0.5% ~ ±1.5mm	Pass
Flatness	ISO 10545-2	±5% ~ ±2.0mm	Pass
Rectangularity	ISO 10545-2	±0.5% ~ ±2.0mm	Pass
Water absorption	ISO 10545-3	0.5% E _p ≥ 3%	Pass
Breaking strength	ISO 10545-4	≥ 1300N	Pass
Modulus of rupture	ISO 10545-4	Ave Minimum 30 N/mm ²	Pass
Resistance to surface abrasion	ISO 10545-7	Complies with Standard	PEI 4
Frost resistance	ISO 10545-12	Complies with Standard	Pass
Thermal shock resistance	ISO 10545-9	Complies with Standard	Pass
Resistance to stain	ISO 10545-14	Min Class 3	Pass
Resistance to chemicals	ISO 10545-14	Min Class B	Pass
Reaction to fire	-	Floor/wall Class A1 FL/A1	Pass

Slip resistance characteristics	Pendulum Dry (4S Slider 96) +36 PTV	Pendulum Wet (4S Slider 96) +36 PTV
Full range		

The colour representations shown in this data sheet are as accurate as the limitations of the printing process will allow. Due to the manufacturing process of our floor tiles there may be a small variation in the PTV value. The slip resistance values are correct at the time of testing and represent the standard production value. Inadequate cleaning and maintenance will lead to significant reduction in the slip resistance of any tiles. The pendulum test results have been displayed in line with H&S Executive guidelines whereby 0-24 represents high slip potential, 25-35 moderate slip potential & 36+ represents a low slip potential.

For further information contact: T: 0116 276 2532 – W: www.parkside.co.uk – E: info@parkside.co.uk

Strata Technical Tiles is the partner brand of Parkside Architectural Tiles