

Rene

14 COLOURS / 1 SIZES / 1 FINISHES / 0 SPECIAL PIECES


Rene is a glass hexagon mosaic collection. It comes in a variety of colours. It also is made from 98% recycled glass! This range is also available in a XL hexagon size.




Rene




Rene




BLACK




ANTHRACITE




GREY




LIGHT BRUN




GAINSBORO




WHITE




GREEN




ROYAL BLUE




LIGHT BLUE



OCHRE




RUSSET



GOLD



SMOKE BLEND



ANCHOR BLEND

Sizes

290x300mm Hex

The colour representations shown in this data sheet are as accurate as the limitations of the printing process will allow. Due to the manufacturing process of our floor tiles there may be a small variation in the PTV value. The slip resistance values are correct at the time of testing and represent the standard production value. Inadequate cleaning and maintenance will lead to significant reduction in the slip resistance of any tiles. The pendulum test results have been displayed in line with H&S Executive guidelines whereby 0-24 represents high slip potential, 25-35 moderate slip potential & 36+ represents a low slip potential.

For further information contact: T: 0116 276 2532 – W: www.parkside.co.uk – E: info@parkside.co.uk

Strata Technical Tiles is the partner brand of Parkside Architectural Tiles

Rene

GROUP / GLASS

	Standard	Requirement	Established values
Surface hardness	ISO 101-92	Declare result	9
Water absorption	ISO 10545-3	Declare result	0%
Frost resistance	ISO 10545-12	Declare result	Resistant
Resistance to stain	ISO 10545-14	Declare Class	Class 5
Resistance to household chemicals and swimming pool salts	ISO 10545-13	Min Class GB	GA
Resistance to high concentrations of alkalis and acids	ISO 10545-13	Declare Value	GHA
Resistance to low concentrations of alkalis and acids	ISO 10545-13	Declare Value	GLA
Resistance to cracking	ISO 10545-11	Declare result	Resistant
Reaction to thermal shock	ISO 10545-9	Declare result	Resistant

Recycled content	%
Rene	98

Grout and trim available

Rene	Grout	Trim

The colour representations shown in this data sheet are as accurate as the limitations of the printing process will allow. Due to the manufacturing process of our floor tiles there may be a small variation in the PTV value. The slip resistance values are correct at the time of testing and represent the standard production value. Inadequate cleaning and maintenance will lead to significant reduction in the slip resistance of any tiles. The pendulum test results have been displayed in line with H&S Executive guidelines whereby 0-24 represents high slip potential, 25-35 moderate slip potential & 36+ represents a low slip potential.

For further information contact: T: 0116 276 2532 – W: www.parkside.co.uk – E: info@parkside.co.uk

Strata Technical Tiles is the partner brand of Parkside Architectural Tiles