

Rigelo

4 COLOURS / 3 SIZES / 2 FINISHES / 0 SPECIAL PIECES

Rigelo is a classic wood effect collection that is versatile enough for most designs. The hues of this collection pay homage to the natural beauty of our forests with cool grey tones and warming hints of brown, replicating both the look and format of real wood planks but with the hardwearing properties of porcelain.



Rigelo



Rigelo



ROBLE



WALNUT



GREY



NOGAL

Porcelain	9.7mm thick	9mm thick	Wall/floor	Interior/exterior
	Matt	Matt	All tiles	All tiles
1195x150	✓		Wall and floor	Interior & exterior
900x150		✓	Wall and floor	Interior & exterior
300x300 Mosaic	✓		Wall and floor	Interior & exterior
75x600 Skirting	✓		Wall	Interior & exterior

Rigelo



OAK MOSAIC



WALNUT MOSAIC



ASH MOSAIC




WHITE MOSAIC

The colour representations shown in this data sheet are as accurate as the limitations of the printing process will allow. Due to the manufacturing process of our floor tiles there may be a small variation in the PTV value. The slip resistance values are correct at the time of testing and represent the standard production value. Inadequate cleaning and maintenance will lead to significant reduction in the slip resistance of any tiles. The pendulum test results have been displayed in line with H&S Executive guidelines whereby 0-24 represents high slip potential, 25-35 moderate slip potential & 36+ represents a low slip potential.

For further information contact: T: 0116 276 2532 – W: www.parkside.co.uk – E: info@parkside.co.uk

Strata Technical Tiles is the partner brand of Parkside Architectural Tiles



Dimensions	Multiple
Finish	Matt
Body	Porcelain
Wall/floor	Wall and floor
Group	Bla
Pendulum Dry	36+
Pendulum Wet	0-24
Recycled content	0-24

	Standard	Requirement	Typical test value
Length and width	ISO 10545-2	$\pm 0.6\% \leq \pm 2\text{mm}$	Pass
Thickness	ISO 10545-2	$\pm 5\% \leq \pm 0.5\text{mm}$	Pass
Straightness	ISO 10545-2	$\pm 0.5\% \leq \pm 1.5\text{mm}$	Pass
Flatness	ISO 10545-2	$\pm 0.5\% \leq \pm 1.5\text{mm}$	Pass
Rectangularity	ISO 10545-2	$\pm 0.5\% \leq \pm 2.0\text{mm}$	Pass
Water absorption	ISO 10545-3	$E_b \leq 0.5\%$	Pass
Breaking strength	ISO 10545-4	$\geq 1300\text{N}$	Pass
Modulus of rupture	ISO 10545-4	Ave Minimum 35 N/mm ²	Pass
Resistance to surface abrasion	ISO 10545-7	n/a	Class 3
Thermal shock resistance	ISO 10545-9	Complies with standard	Pass
Frost resistance	ISO 10545-12	Complies with standard	Pass
Resistance to chemicals	ISO 10545-14	Min Class B	Pass
Resistance to stain	ISO 10545-14	Min Class 3	Pass
Reaction to fire	-	Floor/wall Class A1 FL/A1	Pass

The colour representations shown in this data sheet are as accurate as the limitations of the printing process will allow. Due to the manufacturing process of our floor tiles there may be a small variation in the PTV value. The slip resistance values are correct at the time of testing and represent the standard production value. Inadequate cleaning and maintenance will lead to significant reduction in the slip resistance of any tiles. The pendulum test results have been displayed in line with H&S Executive guidelines whereby 0-24 represents high slip potential, 25-35 moderate slip potential & 36+ represents a low slip potential.

For further information contact: T: 0116 276 2532 – W: www.parkside.co.uk – E: info@parkside.co.uk

Strata Technical Tiles is the partner brand of Parkside Architectural Tiles