

# Sedgwick

6 COLOURS / 1 SIZE / 6 FINISHES / 0 SPECIAL PIECES

Six geometric and three-dimensional surfaces, designed to create architectural spaces using wall tiles that are brought to life by light and shadow. Available in a small size of 50x200mm and available in six stunning colours, Bianco, Terra, Salvia, Powder, Notte and Bordeaux.



Sedgwick



Sedgwick



# Sedgwick

## BIANCO



4100612 PLAIN BIANCO



4100606 DUNE BIANCO



4100604 WAVES BIANCO



\*4100602 STRIP BIANCO



4100610 STUD BIANCO



4100608 PEAK BIANCO

## SALVIA



4100691 PLAIN SALVIA



4100690 DUNE SALVIA



4100688 WAVES SALVIA



\*4100686 STRIP SALVIA




4100687 STUD SALVIA



4100689 PEAK SALVIA

## NOTTE



4100685 PLAIN NOTTE



4100684 DUNE NOTTE



4100682 WAVES NOTTE



\*4100680 STRIP NOTTE



4100681 STUD NOTTE



4100683 PEAK NOTTE

## BORDEAUX



4101164 PLAIN BORDEAUX



4101161 DUNE BORDEAUX



4101160 WAVES BORDEAUX



\*4101159 STRIP BORDEAUX



4101163 STUD BORDEAUX



4101162 PEAK BORDEAUX

## TERRA



4100613 PLAIN TERRA



4100607 DUNE TERRA



4100605 WAVES TERRA



\*4100603 STRIP TERRA



4100611 STUD TERRA



4100609 PEAK TERRA

## POWDER



4101170 PLAIN POWDER



4101167 DUNE POWDER



4101166 WAVES POWDER



\*4101165 STRIP POWDER



4101169 STUD POWDER



4101168 PEAK POWDER


The colour representations shown in this data sheet are as accurate as the limitations of the printing process will allow. Due to the manufacturing process of our floor tiles there may be a small variation in the PTV value. The slip resistance values are correct at the time of testing and represent the standard production value. Inadequate cleaning and maintenance will lead to significant reduction in the slip resistance of any tiles. The pendulum test results have been displayed in line with H&S Executive guidelines whereby 0-24 represents high slip potential, 25-35 moderate slip potential & 36+ represents a low slip potential.

For further information contact: T: 0116 276 2532 – W: [www.parkside.co.uk](http://www.parkside.co.uk) – E: [info@parkside.co.uk](mailto:info@parkside.co.uk)

Strata Technical Tiles is the partner brand of Parkside Architectural Tiles

# Sedgwick

|         |           |            |                   |
|---------|-----------|------------|-------------------|
| Ceramic | 8mm thick | Wall/floor | Interior/exterior |
|         | Matt      | All tiles  | All tiles         |
| 50x200  | ✓         | Wall Only  | Interior Only     |



## GROUP / BIII - CERAMIC

|   | Standard     | Requirement                      | Established Values    |
|---|--------------|----------------------------------|-----------------------|
| Length and Width  | ISO 10545-2  | ±0.5% ~ ±2mm                     | Conforms              |
| Thickness   | ISO 10545-2  | ±5% ~ ±0.5mm                     | Conforms              |
| Straightness  | ISO 10545-2  | ±0.5% ~ ±1.5mm                   | Conforms              |
| Flatness  | ISO 10545-2  | ±0.5% ~ ±2.0mm                   | Conforms              |
| Rectangularity  | ISO 10545-2  | ±0.5% ~ ±2.0mm                   | Conforms              |
| Water Absorption  | ISO 10545-3  | Eb >10%                          | 16 %                  |
| Breaking Strength   | ISO 10545-4  | ≥ 600N                           | ≥ 600N                |
| Modulus of Rupture  | ISO 10545-4  | Ave Minimum 12 N/mm <sup>2</sup> | 28.5N/mm <sup>2</sup> |
| Thermal Shock Resistance                                  | ISO 10545-9  | Pass according to EN ISO 10545-1 | Resistant             |
| Resistance to household chemicals and swimming pool salts | ISO 10545-13 | Min Class GB                     | GA                    |
| Resistance to high concentrations of alkalis and acids    | ISO 10545-13 | Declare Value                    | GHA                   |
| Resistance to low concentrations of alkalis and acids     | ISO 10545-13 | Declare Value                    | GLA                   |
| Resistance to Stain                                       | ISO 10545-14 | Min Class 3                      | Class 5               |
| Reaction to Fire  |              | Class A1 A1/FL                   | Class A1              |

|                  |          |
|------------------|----------|
| Recycled Content | 70 %     |
| Range Name       | Sedgwick |

The colour representations shown in this data sheet are as accurate as the limitations of the printing process will allow. Due to the manufacturing process of our floor tiles there may be a small variation in the PTV value. The slip resistance values are correct at the time of testing and represent the standard production value. Inadequate cleaning and maintenance will lead to significant reduction in the slip resistance of any tiles. The pendulum test results have been displayed in line with H&S Executive guidelines whereby 0-24 represents high slip potential, 25-35 moderate slip potential & 36+ represents a low slip potential.

For further information contact: T: 0116 276 2532 – W: [www.parkside.co.uk](http://www.parkside.co.uk) – E: [info@parkside.co.uk](mailto:info@parkside.co.uk)

Strata Technical Tiles is the partner brand of Parkside Architectural Tiles