

Acrux

7 COLOURS / 1 SIZES / 1 FINISHES / 3 SPECIAL PIECES

Acrux is a range of bespoke ceramic wall tiles that were made specifically for the Royal Exchange development, London. Use these 150x150 tiles together seamlessly to create different laying patterns. This range has 39% recycled content.




Acrux






Acrux



WHITE



GREEN



PEWTER



MUSTARD



HOT PINK



SILVER




BLUE

Ceramic	10mm	Wall/floor	Interior/exterior
	Gloss	All tiles	-
150X150	✓	Wall only	-

The colour representations shown in this data sheet are as accurate as the limitations of the printing process will allow. Due to the manufacturing process of our floor tiles there may be a small variation in the PTV value. The slip resistance values are correct at the time of testing and represent the standard production value. Inadequate cleaning and maintenance will lead to significant reduction in the slip resistance of any tiles. The pendulum test results have been displayed in line with H&S Executive guidelines whereby 0-24 represents high slip potential, 25-35 moderate slip potential & 36+ represents a low slip potential.

For further information contact: T: 0116 276 2532 – W: www.parkside.co.uk – E: info@parkside.co.uk

Strata Technical Tiles is the partner brand of Parkside Architectural Tiles



150x150

GROUP / BIII - CERAMIC

	Standard	Requirement	Established values
Length and width	ISO 10545-2	$\pm 0.6\% \sim \pm 2\text{mm}$	Conforms
Thickness	ISO 10545-2	$\pm 10\% \sim \pm 0.5\text{mm}$	Conforms
Straightness	ISO 10545-2	$\pm 0.5\% \sim \pm 1.5\text{mm}$	Conforms
Flatness	ISO 10545-2	$\pm 0.5\% \sim \pm 2.0\text{mm}$	Conforms
Rectangularity	ISO 10545-2	$\pm 0.5\% \sim \pm 2.0\text{mm}$	Conforms
Water absorption	ISO 10545-3	$E_b \leq 10\%$	Ave < 6%
Breaking strength	ISO 10545-4	$\geq 600\text{N}$	$\geq 1000\text{N}$
Modulus of rupture	ISO 10545-4	Ave min 12 N/mm ²	Ave min 22 N/mm ²
Thermal shock resistance	ISO 10545-9	Pass according to EN ISO 10545-1	-
Frost resistance	ISO 10545-12	Pass according to EN ISO 10545-1	-
Resistance to household chemicals and swimming pool salts	ISO 10545-13	Min Class GB	GA
Resistance to high concentrations of alkalis and acids	ISO 10545-13	Declare Value	NPD
Resistance to low concentrations of alkalis and acids	ISO 10545-13	Declare Value	NPD
Resistance to stain	ISO 10545-14	Declare Value	Class 5
Reaction to fire	-	Class A1 A1/FL	A1 A1/FL

Recycled content	%
Acrux	39