

Boston

6 COLOURS / 3 SIZES / 1 FINISH / 0 SPECIAL PIECES

Ranging in size from 30x60cm to 60x120cm, Boston's neutral tones lend a contemporary edge to any space. Produced in a single calibre with rectified edges, each of the three sizes can be used in conjunction with each other to create a unique modular design. Its PTV +36 rating means it has high slip resistance making it suitable for commercial indoor and outdoor spaces.





Boston




Boston



Porcelain	8mm thick	Wall/floor	Interior/exterior
	Matt	All tiles	All tiles
296x595	✓	Wall & Floor	Interior & Exterior
595x595	✓	Wall & Floor	Interior & Exterior
595x119.5	✓	Wall & Floor	Interior & Exterior



296x595x8



595x595x8

595x119.5x8

The colour representations shown in this data sheet are as accurate as the limitations of the printing process will allow. Due to the manufacturing process of our floor tiles there may be a small variation in the PTV value. The slip resistance values are correct at the time of testing and represent the standard production value. Inadequate cleaning and maintenance will lead to significant reduction in the slip resistance of any tiles. The pendulum test results have been displayed in line with H&S Executive guidelines whereby 0-24 represents high slip potential, 25-35 moderate slip potential & 36+ represents a low slip potential.

For further information contact: T: 0116 276 2532 – W: www.parkside.co.uk – E: info@parkside.co.uk

Strata Technical Tiles is the partner brand of Parkside Architectural Tiles

Boston

GROUP / BLA - PORCELAIN

	Standard	Requirement	Established Values
Length and Width	ISO 10545-2	±0.6% ~ ±2mm	Conforms
Thickness	ISO 10545-2	±5% ~ ±0.5mm	Conforms
Straightness	ISO 10545-2	±0.5% ~ ±1.5mm	Conforms
Flatness	ISO 10545-2	±0.5% ~ ±2.0mm	Conforms
Rectangularity	ISO 10545-2	±0.5% ~ ±2.0mm	Conforms
Water Absorption	ISO 10545-3	$E_b \leq 0.5\%$	$\leq 0.1\%$
Breaking Strength	ISO 10545-4	$\geq 1300N$	$S \geq 1500N$
Modulus of Rupture	ISO 10545-4	Ave Minimum 35 N/mm ²	$R \geq 40 N/mm^2$
Resistance to deep abrasion (unglazed tiles)	ISO 10545-6	$\leq 175mm^3$	$\leq 150mm^3$
Thermal Shock Resistance	ISO 10545-9	Pass according to EN ISO 10545-1	Resistant
Frost Resistance	ISO 10545-12	Pass according to EN ISO 10545-1	Resistant
Resistance to household chemicals and swimming pool salts	ISO 10545-13	Min Class GB	GA
Resistance to high concentrations of alkalis and acids	ISO 10545-13	Declare Value	GHA
Resistance to low concentrations of alkalis and acids	ISO 10545-13	Declare Value	GLA
Resistance to Stain	ISO 10545-14	Declare Value	5
Reaction to Fire		Class A1 A1/FL	A1 A1/FL

Slip Resistance Characteristics	Pendulum Dry (4S Slider 96) +36	Pendulum Wet (4S Slider 96) +36
Full Range	✓	✓

Recycled Content	%
Boston	10%

The colour representations shown in this data sheet are as accurate as the limitations of the printing process will allow. Due to the manufacturing process of our floor tiles there may be a small variation in the PTV value. The slip resistance values are correct at the time of testing and represent the standard production value. Inadequate cleaning and maintenance will lead to significant reduction in the slip resistance of any tiles. The pendulum test results have been displayed in line with H&S Executive guidelines whereby 0-24 represents high slip potential, 25-35 moderate slip potential & 36+ represents a low slip potential.

For further information contact: T: 0116 276 2532 – W: www.parkside.co.uk – E: info@parkside.co.uk

Strata Technical Tiles is the partner brand of Parkside Architectural Tiles