

Connect

11 COLOURS / 1 SIZE / 2 FINISHES / 0 SPECIAL PIECES

Connect unites the strength of its right angle with a sinuous wave that invites us to rise, to ascend. A design with a lot of personality which does not go unnoticed. Connect invites you to play with its multiple possibilities, to break the curve or give it continuity and combine its two matt and gloss finishes. In a 8.3x12cm size, this is a very playful wall tile choice.



Connect



Connect



Connect



YELLOW

TURQUOISE

RUBY

PINK

ORANGE



INK BLUE

GREY

GREEN

BLACK

AQUA

WHITE

White body ceramic	6mm thick	Wall/floor	Interior/exterior
	All tiles	All tiles	All tiles
83x120	Gloss & Matt	Wall	Interior

The colour representations shown in this data sheet are as accurate as the limitations of the printing process will allow. Due to the manufacturing process of our floor tiles there may be a small variation in the PTV value. The slip resistance values are correct at the time of testing and represent the standard production value. Inadequate cleaning and maintenance will lead to significant reduction in the slip resistance of any tiles. The pendulum test results have been displayed in line with H&S Executive guidelines whereby 0-24 represents high slip potential, 25-35 moderate slip potential & 36+ represents a low slip potential.

For further information contact: T: 0116 276 2532 – W: www.parkside.co.uk – E: info@parkside.co.uk

Strata Technical Tiles is the partner brand of Parkside Architectural Tiles

Connect

GROUP / BIII - CERAMIC

	Standard	Requirement	Established values
Length and width	ISO 10545-2	±0.75mm	Conforms
Thickness	ISO 10545-2	±5mm	Conforms
Straightness	ISO 10545-2	±0.5mm	Conforms
Flatness	ISO 10545-2	+0.75mm	Conforms
Rectangularity	ISO 10545-2	±0.75mm	Conforms
Water absorption	ISO 10545-3	$E_b > 10\%$	Ave >10%
Breaking strength	ISO 10545-4	≥ 600N	≥ 600N
Modulus of rupture	ISO 10545-4	Ave Minimum 12 N/mm ²	Ave min 12 N/mm ²
Thermal shock resistance	ISO 10545-9	Pass according to EN ISO 10545-1	Resistant
Resistance to household chemicals and swimming pool salts	ISO 10545-13	Min Class GB	GA
Resistance to high concentrations of alkalis and acids	ISO 10545-13	Declare Value	GHB
Resistance to low concentrations of alkalis and acids	ISO 10545-13	Declare Value	GLA
Resistance to stain	ISO 10545-14	Min Class 3	Class 5
Reaction to fire	-	Class A1 A1/FL	A1 A1/FL

Recycled content	%
Connect	54

The colour representations shown in this data sheet are as accurate as the limitations of the printing process will allow. Due to the manufacturing process of our floor tiles there may be a small variation in the PTV value. The slip resistance values are correct at the time of testing and represent the standard production value. Inadequate cleaning and maintenance will lead to significant reduction in the slip resistance of any tiles. The pendulum test results have been displayed in line with H&S Executive guidelines whereby 0-24 represents high slip potential, 25-35 moderate slip potential & 36+ represents a low slip potential.

For further information contact: T: 0116 276 2532 – W: www.parkside.co.uk – E: info@parkside.co.uk

Strata Technical Tiles is the partner brand of Parkside Architectural Tiles