

Woodcraft

8 COLOURS / 1 SIZE / 1 FINISH / 0 SPECIAL PIECES

Woodcraft's classic parquet look brings a smart finish to commercial interiors. In a range of warm and neutral natural tones, this porcelain floor and wall tile's authentic wood block pattern is instantly familiar yet unusual, making a stand-out feature. Authenticity is heightened with a matt finish and variation. Rated 36+ PTV and suitable for outdoor use, Woodcraft comes in a versatile 20x20cm format.



Woodcraft




Woodcraft



Woodcraft



Porcelain	8.3mm thick	W all/floor	Interior/exterior
	Matt	All tiles	All tiles
200x200	a	Wall & Floor	Interior & Exterior



200x200x8.3

The colour representations shown in this data sheet are as accurate as the limitations of the printing process will allow. Due to the manufacturing process of our floor tiles there may be a small variation in the PTV value. The slip resistance values are correct at the time of testing and represent the standard production value. Inadequate cleaning and maintenance will lead to significant reduction in the slip resistance of any tiles. The pendulum test results have been displayed in line with H&S Executive guidelines whereby 0-24 represents high slip potential, 25-35 moderate slip potential & 36+ represents a low slip potential.

For further information contact: T: 0116 276 2532 – W: www.parkside.co.uk – E: info@parkside.co.uk

Strata Technical Tiles is the partner brand of Parkside Architectural Tiles

Woodcraft

GROUP / BLA - PORCELAIN

	Standard	Requirement	Established values
Length and width	ISO 10545-2	±0.6% ~ ±2mm	Conforms
Thickness	ISO 10545-2	±5% ~ ±0.5mm	Conforms
Straightness	ISO 10545-2	±0.5% ~ ±1.5mm	Conforms
Flatness	ISO 10545-2	±0.5% ~ ±2.0mm	Conforms
Rectangularity	ISO 10545-2	±0.5% ~ ±2.0mm	Conforms
Water absorption	ISO 10545-3	Eb ≤ 0.5%	Ave ≤ 0.5%
Breaking strength	ISO 10545-4	≥ 1300N	≥ 1300N
Modulus of rupture	ISO 10545-4	Ave Minimum 35 N/mm ²	> 35 N/mm ²
Resistance to deep abrasion (glazed tiles)	ISO 10545-7	Declare value	PEI - 3
Thermal shock resistance	ISO 10545-9	Pass according to EN ISO 10545-1	Resistant
Frost resistance	ISO 10545-12	Pass according to EN ISO 10545-1	Resistant
Resistance to household chemicals and swimming pool salts	ISO 10545-13	Min Class GB	GA
Resistance to high concentrations of alkalis and acids			NPD
Resistance to low concentrations of alkalis and acids	ISO 10545-13	Declare Value	
Resistance to stain	ISO 10545-13	Declare Value	GLA
Reaction to fire	ISO 10545-14	Declare Value	Class 5
		Class A1 A1/FL	A1 A1/FL

Slip resistance characteristics	Pendulum Dry (4S Slider96) +36 PTV	Pendulum Wet (4S Slider96) +36 PTV
Full range	√	√

Recycled content	%
Woodcraft	7

The colour representations shown in this data sheet are as accurate as the limitations of the printing process will allow. Due to the manufacturing process of our floor tiles there may be a small variation in the PTV value. The slip resistance values are correct at the time of testing and represent the standard production value. Inadequate cleaning and maintenance will lead to significant reduction in the slip resistance of any tiles. The pendulum test results have been displayed in line with H&S Executive guidelines whereby 0-24 represents high slip potential, 25-35 moderate slip potential & 36+ represents a low slip potential.

For further information contact: T: 0116 276 2532 – W: www.parkside.co.uk – E: info@parkside.co.uk

Strata Technical Tiles is the partner brand of Parkside Architectural Tiles